



## TECHNICAL DATA

### MASSES

Operating mass (incl. Cab)	20,300 Kg
Operating mass (incl. ROPS)	20,160 Kg
Module mass front /rear (incl. Cab)	13,800 Kg /6,500 Kg
Module mass front /rear (incl. ROPS)	13,800 Kg /6,360 Kg
Max mass (incl. Cab)	21,800 Kg
Max mass (incl. ROPS)	21,800 Kg

### COMPACTION

Static linear load	64.8 kg/cm
Nominal amplitude (high/low)	1.8/1.1 mm
Vibration frequency (high/low amplitude)	30/31 Hz
Centrifugal force (high/low amplitude)	339/231 KN

### TRACTION

Speed range	0-11 km/h
Tyre size	23.1x26
Max. theoretical gradeability	44 %
Vertical oscillation	±9°

### ENGINE

Manufacturer/Model	CUMMINS 6BTAA5.9 II/T2
Type	Water cooled turbo Diesel
Rated power, SAE J1995	153kW@2200rpm
Fuel tank capacity	320 l

### ENGINE

Manufacturer/Model	CUMMINS QSB5.9 IIIA/T3
Type	Water cooled turbo Diesel
Rated power, SAE J1995	154kW@2400rpm

### ENGINE



Manufacturer/Model	CUMMINS B5.9 CSIV
Type	Water cooled turbo Diesel
Rated power, SAE J1995	154kW@2200rpm

### HYDRAULIC SYSTEM

Driving	Axial piston pump with variable displacement. Axial piston motors with variable displacement.
Vibration	Axial piston pump with variable displacement. Axial piston motors with constant displacement.
Steering	Gear pump with constant displacement.
Service brake	Hydrostatic in forward and reverse lever.
Parking/ Emergency brake	Failsafe multidisc brake in drum gear box and in rear axle.

Find us locally at [www.dynapac.com](http://www.dynapac.com)

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all information's are supplied without liability.



## DIMENSIONS

### DIMENSIONS

A. Wheelbase	3,100 mm
B1. Width, front	2,360 mm
B2. Width, rear	2,130 mm
D. Drum diameter	1,573 mm
H1. Height, with ROPS/cab	2,900 mm
H2. Height, w/o ROPS/cab	2,145 mm
K1. Ground clearance	470 mm
K2. Curb clearance	500 mm
L. Length	6,236 mm
O1. Overhang, right	130 mm
O2. Overhang, left	100 mm
R1. Turning radius, outside	5,630 mm
R2. Turning radius, inside	3,500 mm
S. Drum shell thickness	50 mm
W. Drum width	2,130 mm
$\alpha$ . Steering angle	$\pm 38^\circ$

Find us locally at [www.dynapac.com](http://www.dynapac.com)

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all information's are supplied without liability.